

APDatec 910 blaugedeckt

Single layer Polyamide tube of PA 11/12

- Applications** pneumatics, automation technology & robotics, welding technology, vehicle construction, compressors
- Structure** PA, blue, opaque
- Temperature** -40°C up to 90°C
- Properties** good temperature resistance, high pressure resistance, smooth inside, smooth outside



Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Betriebsdruck Max. (bar)	Total Weight per Item (kg)	Length	Article Number
2	4	1,00	20	40,00	1,00	100	910B0041000
2	4	1,00	20	40,00	0,50	50	910B0041050
3	5	1,00	25	35,00	1,35	100	910B0051000
4	6	1,00	30	25,00	1,60	100	910B0061000
4	6	1,00	30	25,00	0,80	50	910B0061050
6	8	1,00	40	20,00	2,26	100	910B0081000
6	8	1,00	40	20,00	1,13	50	910B0081050
8	10	1,00	60	15,00	3,00	100	910B0101000
9	12	1,50	75	17,00	2,65	50	910B0121550
10	12	1,00	60	13,00	1,80	50	910B0121050
11	14	1,50	85	14,00	6,20	100	910B0141500
27	4	0,65	20	30,00	0,50	50	910B0040650