

APDatec 910 schwarz

Single layer Polyamide tube of PA 11/12

- Applications** pneumatics, vehicle construction, compressors, automation technology & robotics, compressed air
- Structure** PA, black, opaque
- Temperature** -40°C up to 90°C
- Properties** good temperature resistance, , smooth outside, smooth inside



Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Betriebsdruck Max. (bar)	Total Weight per Item (kg)	Length	Article Number
2	4	1,00	20	40,00	1,00	100	910S0041000
2	4	1,00	20	40,00	0,50	50	910S0041050
4	6	1,00	30	25,00	1,60	100	910S0061000
4	6	1,00	30	25,00	0,40	25	910S0061025
4	6	1,00	30	25,00	0,80	50	910S0061050
6	8	1,00	40	20,00	2,26	100	910S0081000
6	10	2,00	50	20,00	5,30	100	910S0102000
6	10	2,00	50	20,00	2,65	50	910S0102050
8	10	1,00	60	15,00	3,00	100	910S0101000
8	10	1,00	60	15,00	1,50	50	910S0101050
8	12	2,00	80	40,00	6,60	100	910S0122000
10	12	1,00	60	13,00	1,80	50	910S0121050
11	14	1,50	85	14,00	6,20	100	910S0141500
11	14	1,50	85	14,00	3,10	50	910S0141550
12	15	1,50	90	15,00	6,20	100	910S0151500
27	4	0,65	20	30,00	0,36	50	910S0040650